

Scientific American



AN ILLUSTRATED

JOURNAL OF ART, SCIENCE & MECHANICS

VOL. XIV



NEW-YORK

PUBLISHED BY MUNN & CO.

pi
47
to
pu
pa
ob
su
ge
si
pl
un
vi
ho
ed
ca
ha
im
gu
tr
pu
w
of
re
an
th
tr
in
m
fr
sh
sh
cu
on
cu
in
ra
ed
ot
th
by
an
m
sa
to
ti
do
zo
ing
sc
de
an
me
me
su
po
fe
of
be
wh
co
zo
M
wi



Scientific American.

LIBRARY
OF THE
UNIVERSITY

THE ADVOCATE OF INDUSTRY, AND JOURNAL OF SCIENTIFIC, MECHANICAL AND OTHER IMPROVEMENTS.

VOL XIV.

NEW YORK, SEPTEMBER 11, 1858.

NO. 1.

THE SCIENTIFIC AMERICAN,

PUBLISHED WEEKLY

At No. 128 Fulton street, (Sun Buildings), New York,
BY MUNN & CO.

O. D. MUNN, S. H. WALES, A. E. BEACH.

Responsible Agents may also be found in all the principal cities and towns of the United States.

Sampson Low, Son & Co., the American Booksellers, 47 Ludgate Hill, London, Eng., are the British Agents to receive subscriptions for the SCIENTIFIC AMERICAN.

Single copies of the paper are on sale at the office of publication, and at all the periodical stores in this city, Brooklyn and Jersey City.


TERMS—Two Dollars per annum.—One Dollar in advance, and the remainder in six months.

See Prospectus on last page. No Traveling Agents employed.

New Circular Sawing Machine.

This invention consists in sawing rectangular pieces of timber, laths and strips for various purposes direct from the log, by arranging a pair of circular saws at right angles to each other, and operating and adjusting them in such a manner as to enable them to act together at the same time, and any desired sized strip to be cut from the log by the simple act of moving the log in either direction under the saws.

Our illustration represents a perspective view of the machine, in which A is the lower horizontal frame, on one end of which is erected another frame, B, consisting of four vertical posts secured by cap pieces at top, and having a horizontal transverse rising and falling frame, C, in front, provided with V-shaped guides, c d, which frame is arranged on a transversely moving frame, D. To the front part of the frame, D, are secured boxes in which is suspended the vertical shaft, G, of the horizontal circular saw, H, which receives its motion from a band passing around a pulley near the upper end of the saw shaft, and around a horizontal transverse drum, E, whose journals turn in suitable boxes, F, at the rear of the machine. Immediately below the vertical frame, D, and slightly in the rear of the saw shaft, G, is arranged a horizontal transverse shaft, I, which turns in suitable boxes secured to the lower part of said frame, D, on the end of which horizontal shaft is secured a vertical circular saw, J, corresponding in every respect with the saw, H, but arranged at right angles to it, with the cutting edges of the two in such relation to each other as to cut out a perfect right angle from the log when operated. The saw, J, is driven by a band passing around a pulley on its shaft, and around the drum, E, at the rear of the machine, and the edge of the two saws, H J, are adjusted to the proper relation to each other, by sliding the boxes of the vertical shafts, G, in vertical grooves formed in dovetail tongued blocks, which have a horizontal movement in grooves formed in projecting pieces secured to the frame, D; suitable screws being provided to secure them at the desired positions. The horizontal frame, C, and its attachments, have an up and down movement over suitable ways or guides, a, by means of vertical screw rods, K, secured in suitable boxes in front of the upright front posts of the frame, B, and passing through female screws formed in or secured to the ends of the frame, G, which screw shafts, K, have bevel cog wheels, L, on their upper ends, which mesh in gear with corresponding bevel cog wheels, M, secured in the ends of horizontal shafts, O, having similar cog wheels, M, at their opposite ends which mesh in gear with similar bevel cog wheels, L, at this end,



which also mesh in gear with the bevel cog wheels in a horizontal transverse shaft, on which is secured a pulley, P, having loose pulleys, P' P', on either side of it. Around these pulleys pass bands, Q Q', one of which is twisted, and both of which pass around a pulley or drum, R, on the main horizontal driving shaft, S, which shaft is also provided at its end with a band wheel for receiving the motive power band, and a smaller pulley, T, around which is passed a band, U, also passing around a pulley, V, turning loosely on the horizontal transverse shafts which give the required traversing movement to the log carriage, by respectively transferring it from the loose pulley to either of the pulleys, W, secured respectively upon the hollow shaft by which the carriage is moved in one direction, and upon the shaft which passes through the same for giving a reverse movement to the carriage.

The vertical frame, D, and its attachments, is moved transversely in order to regulate the width of the piece of timber to be cut, by means of a horizontal bar, b, passing through guide openings in ears secured to the end of the frame, C, and the back of the frame, D, and having a handle, e, at its end, by which with the aid of a clamp screw, f, a traversing movement can be given it, the distance between the shoulders secured on it, and the

guiding ear at one end arranged between said shoulders, in the following manner: Suppose it is desired to increase the width of the board or strip of timber to be cut from the log, the clamp screw is pressed upon the rod, i, and the said rod is drawn outward by its handle, as far as the shoulder on it between the guide ear near its end, and the frame, D, will permit, the said rod bringing with it the frame, D, circular saws and other attachments. The screw, f, is then unclamped, and the rod, b, is forced past it in a reverse direction until the shoulder on said rod, between the guide ear and handle, is again in contact with said ear, when the screw, f, is again clamped on the rod, b, and the operation repeated until the frame, D, and saws, H J, are moved the required distance when the screw f is firmly clamped upon the rod, b, to secure the frame, D.

From a careful perusal of the foregoing description, the operation will be readily understood. The motive power is applied to the shaft, S, and from it power is transmitted respectively to the wheels, V W W, as occasion may require, by the band, V, its transfer to either being effected by the bar, X, and lever, Z, so as to give a motion either way to the carriage and log or timber from which the slats are to be cut. In case it is desired to raise or lower the horizontal frame, C, and

saws, H J, and other attachments, one of the bands, Q Q', as the case may be, is transferred from the loose pulleys, P' P', to the pulley, P, until the gage bar at the end of the frame, C, indicates on the graduated plate the desired height, when both bands, Q Q', are again made to surround the loose pulleys, P' P'.

This machine, to whose efficient action we can testify from personal observation, was patented December 29, 1857, by E. H. Dewitt, of Xenia, Ohio, and any further information can be had by addressing B. N. Strong, D. B. Tiffany, and Dr. J. G. Kyle, Xenia, Ohio, or Daniel Strong, Wethersfield, Conn.

Tanneries.

According to official statistics there are 6,263 tanneries in the United States, of which the south has about one-third. Pennsylvania alone has nearly one-sixth part of the whole number, or 1,039. The southern States rank in the following order:—Tennessee has 394; Virginia, 341; Kentucky, 275; North Carolina, 151; Alabama, 149; Missouri, 148; Georgia, 140; Maryland, 116; Mississippi, 92; South Carolina, 91; Arkansas, 51; and the other southern States a less number each. The entire capital invested in all the tanneries in the land is \$18,900,557, the number of skins in them being 2,658,065, and the number of sides of leather counting up 12,257,940.



Issued from the United States Patent Office
FOR THE WEEK ENDING AUGUST 31, 1858.

[Reported officially for the Scientific American.]

* Circles giving full particulars of the mode of applying for patents, size of model required, and much other information useful to inventors, may be had gratis by addressing MUNN & CO., Publishers of the SCIENTIFIC AMERICAN, New York.

COUPLING FOR BALE HOOPS—John Agnew, of Columbus, S. C.: I claim the socket, A, provided with the double taper opening, a, in connection with the loops, b, at the ends, B, of the hoops, substantially as and for the purposes set forth.

HILLTOP PLOWS—H. S. Akins, of Speedsville, N. Y.: I do not claim, broadly, the combination of the reversible mold board with the adjustable colter.

But I claim, first, The reversible moldboard and colter, A, and the adjustable colter, B, in the manner and for the purposes substantially as described.

Second. Attaching the hook, L, to the lever, I, which operates the colter, E, thereby making the operation both of the moldboard and colter in their respective positions by one and the same hook, and at one operation as set forth.

Third. The reversible chain clevis, O, for the purpose of producing reversible side draft, when connected and operated in the manner substantially as described.

MACHINES FOR CLEANING HOSE, &c.—John B. Alden, Jr. and E. L. Gates, of Worcester, Mass.: We are aware that revolving brushes are not new, and do not claim such, as they have been used, but only when constructed and operating as described.

We claim the combination and arrangement of the brushes, one or both of which is movable to and from the other during operation, and the rolls, F F I, when constructed and operating in the manner and for the purposes substantially as described.

COTTON SEED PLANTERS—H. P. Allen, of Bowling Green, Ky.: I claim, first, The combination of the hook, when arranged to reciprocate, with rotating ratchet wheel and pall or such equivalent device as will enable the fireman to operate said scraper by hand, or connect it to some part of the engine so that it will be operated by it, substantially as described.

I also claim the pipe or spout, K, for conducting the soot and sparks from the spark arrester or smoke stack, substantially as described.

SEWING MACHINES—Solomon Andrews, of Perth Amboy, N. J.: I am aware that the square or parallelogram motion has been employed for feeding the cloth in sewing machines, therefore I do not claim this movement.

But I claim the combination of the wedge and lever piece, Fig. 7, and feeding foot, Fig. 3, constructed and operating in the manner substantially as described for the purpose specified.

SECURING PLANE IRONS TO THE STOCKS OF BENCH PLANES—Leonard Baile, of Winchester, Mass.: I claim the application and arrangement of one or more bearers, F, the clamp lever, G, and the thumb cam, H, together and with respect to the top surface of the plane-iron and the bearing surface or cutter seat, d, of the throat, substantially as represented and described.

LOCKS FOR WEAVING SKIRT FRINGE—James Beck, of New York City: I claim the employment of shears in combination with the rod around which the fringe threads are carried, substantially as described, for the purpose of cutting the said threads on the rod, as set forth.

UMBRELLAS—Charles Boernicke, of Baltimore, Md.: I claim constructing a pocket umbrella as described, consisting of rods, D D D 2, E F G, joint lever, n 5 p, collar piece, a 5, rod, C, with projection, m, stick, n, A 2 A 3, provided with disks, a 1 1 2 and lever, b, with springs, c, all combined and operated as set forth.

SEEDING MACHINES—T. J. Bottoms, of Thomastonville, Ga.: I claim the eccentric pin, i, lever, d, spring, e, valve, m, spreader, n, rag pin, l, slide, o, and hopper, h, the w ole arranged and operating as described for the purposes specified.

PORTABLE FENCE—R. J. Brown, of Perry, Pa.: I claim constructing a portable fence, without posts, by connecting together a series of strands of twisted tenons and gains in the manner specified. Also, in combination with the above, the use of right and left hand-screws, in the manner and for the purpose specified.

SEEDING PLANE IRONS TO THE STOCKS OF BENCH PLANES—Leonard Baile, of Winchester, Mass.: I claim the application and arrangement of one or more bearers, F, the clamp lever, G, and the thumb cam, H, together and with respect to the top surface of the plane-iron and the bearing surface or cutter seat, d, of the throat, substantially as represented and described.

STEAM COOK—Albert Fuller, of Cincinnati, Ohio: I am aware that elastic plugs or valves have been previously used for steam cocks, and that nuts have been arranged or applied to them for the purpose of expanding them.

But I am not aware that any have been arranged like the one described, with a shield and cap, for the purpose of not only expanding the plug when necessary, but also preventing abrasion, and the plug from being forced through the valve seat by the pressure of steam. I therefore do not claim broadly the elastic plug, E.

But I claim placing the elastic plug, E, on the valve seat, D, between the metallic shield, g, and cap, h, the parts being arranged relatively with respect to each other, substantially as and for the purpose set forth.

TOP ROLLERS FOR SPINNING MACHINES—Charles Greene, of Salem, Mass.: I claim the application of a top roller of a spinning machine to its spindle, so as to be capable of revolving and rotating them substantially in manner and for the purpose specified.

METHOD OF STRETCHING BOOTS AND SHOES—George W. Griswold, of Carbondale, Pa.: I claim stretching boots or shoes from the outside, and at any part or point, without stretching other parts or points by means of a skeleton last on the inside and a pressing apparatus, substantially such as that described, on the outside of said shoe or boot.

PORTABLE HOUSE BELL—Albert W. Hale, of New Britain, Conn.: I claim a spring hammer tongue, E, provided with a projection, g, so arranged as to be operated upon by a pin, e, attached to an arbor, C, for the purpose set forth.

DRAWING BOARDS—Isaac P. Hansell, of Springfield, Ill.: I claim the stripe, B, placed at each side of the board, A, and having their outer edges curved, or made of concave form, in the manner described, and used in connection with the square having its blade, C, and head, D, arranged relatively with respect to each other, as set forth, the whole being for the purpose specified.

MILLS FOR SUGAR CANE—Jeremiah Howard, of New York City: I claim the employment or use of a pump, G, water reservoir, F, and valves, g, in connection with necessary pipes, H I, and cylinder, E, provided with piston, D, acting on the bearing of the slider or rollers, the whole being arranged as shown or in any equivalent way, so as to operate as and for the purpose set forth.

ROTARY PUMPS—Levi Burnell, of Milwaukee, Wis.: I claim operating the double sets of radially sliding pistons, d d' and f f', in directions at right angles to each other by means of the three-sided stationary cam, g, the rotating cam box, b b', and the cam yokes, c e, arranged and operating with each other in the manner set forth.

MANUFACTURING SHEARS—Wm. S. Butler, of Rocky Hill, Conn.: I claim as a new article of manufacture a pair of shears made of cast iron, with their cutting edges, A', hardened or tempered in the manner described.

LOCK-JOINT FASTENER FOR STUDS, &c.—Ira A. Ives, of New York City: I do not wish to be understood as limiting any claim of invention to the two special modes of application described, as no doubt, other modes of applying the principle of my invention may be devised.

What I claim is the spring hinged pin, in combination with the recess, substantially as described, and for the purpose specified.

RECEMPTENT CHAIR—David Burzell, of Charleston, Mass.: I claim the arrangement and application of a lever, E, and notched cams, F G, to either or both sides of the seat frame, A, and to the back, B, and leg rest, D, substantially as explained and as represented in the drawings.

PRINTERS' COMPOSING STICKS—Alexander Calhoun, of Hartford, Conn.: I claim the application of the plate, B, in the manner and for the purpose substantially as set forth and described.

SEWING MACHINES—D. W. Clark, of Bridgeport, Ct.: I claim imparting the necessary intermittent motion to the wheel, M, by means of an endless belt, O, and vibratory, Q Q', arranged and operating in the manner, substantially as described.

SEEDING MACHINES—Smith Conklin and George Newton, of Sterling, Ill.: We do not claim, broadly, a perforated reciprocating slide without reference to the form or shape of the perforation and the gauge or regulating bar, H, for such device is common to many classes of seeding machines.

But we claim the arrangement and combination of the plate, F, guides, C, bars, G H, and box, E, as for the purposes shown and described.

SUN SHADES—A. G. Davis, of Watertown, Conn.: I do not claim, broadly, forming an extension handle of two rods, one rod sliding within the other, for this is a well-known means that is employed for the handles of various tools and implements.

But I claim the rod, A, provided with the hub or base, B, and the pressure bar and stop, f, in connection with the hollow or tubular rod, E, provided with the ferrule, E', the above parts being arranged in relation with the frame, B, and slide, D, substantially as and for the purpose set forth.

CARPET FASTENERS—Morris Dewey and Ira Phillips, of Clarendon, N. Y.: We claim the pin and the set as described, combined and arranged for fastening carpets to floors in the manner specified.

RAILROAD CAR STATE—John C. De Witt, of Brooklyn, N. Y.: I claim sustaining the bottoms, C, of the car seats on the slotted corners of the oscillating cradles, A, capable of being turned on horizontal transverse shafts, B, and combining and arranging therewith slotted bars, G, connected at their upper ends to the hacks, I, of the seats, by bars, H, and oscillating levers, K, and movable trucks, L, with tilting platforms, O, in such a manner as to enable the seats to be sustained and secured in the proper position to accommodate the passengers in a sitting posture, or their bottoms, D, and backs, I, to be brought to the proper angle of inclination of the tilting platforms, O, and in relation to each other to form a series of reclining couches or berths, substantially as set forth.

LAMPS—James P. Kenyon and Ellen Kenyon, of Bronx, N. Y.: We claim, first, The described arrangement and combination of the wheel, C, with the devices as described.

But I claim furnishing the side of the lamp shade with the groove or recess, 4, when the spreading flange, y y, is arranged therewith in the manner represented, for the purpose of preventing the end of the lumber when being sawed from butting against or catching to the end of the said flange, as mentioned in the specification.

METHOD OF ATTACHING THE SPREADER TO SAWS OF CIRCULAR SAWING MACHINES—William D. Levitt, of Cincinnati, Ohio: I do not wish to be understood as claiming the spreading flange when taken separately.

But I claim furnishing the side of the saw plate with the groove or recess, 4, when the spreading flange, y y, is arranged therewith in the manner represented, for the purpose of preventing the end of the lumber when being sawed from butting against or catching to the end of the said flange, as mentioned in the specification.

LOCK—John P. Lord, of Manchester, N. H.: I claim first, The application of the guides, a a a e, or their equivalents, also the groove, B, and spring, C, or their equivalents, substantially as specified.

Second. The application of the tongue, D, and guards E E E E, or their equivalents, combined with the bolt, n, substantially as specified.

Third. The application of the slotted stud, substantially as specified.

Fourth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Fifth. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Sixth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Seventh. The application of the slotted stud, substantially as specified.

Eighth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Ninth. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Tenth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Eleventh. The application of the slotted stud, substantially as specified.

Twelfth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Thirteenth. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Fourteenth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Fifteenth. The application of the slotted stud, substantially as specified.

Sixteenth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Seventeenth. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Eighteenth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Nineteenth. The application of the slotted stud, substantially as specified.

Twenty. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Twenty-first. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Twenty-second. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Twenty-third. The application of the slotted stud, substantially as specified.

Twenty-fourth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Twenty-fifth. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Twenty-sixth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Twenty-seventh. The application of the slotted stud, substantially as specified.

Twenty-eighth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Twenty-ninth. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Thirtieth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Thirty-first. The application of the slotted stud, substantially as specified.

Thirty-second. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Thirty-third. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Thirty-fourth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Thirty-fifth. The application of the slotted stud, substantially as specified.

Thirty-sixth. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Thirty-seventh. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Thirty-eighth. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Thirty-ninth. The application of the slotted stud, substantially as specified.

Forty. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Forty-one. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Forty-two. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Forty-three. The application of the slotted stud, substantially as specified.

Forty-four. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Forty-five. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Forty-six. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Forty-seven. The application of the slotted stud, substantially as specified.

Forty-eight. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Forty-nine. The application of the slotted stud, substantially as specified.

Forty-nine. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Forty-nine. The application of the slotted stud, substantially as specified.

Forty-nine. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Forty-nine. The application of the slotted stud, substantially as specified.

Forty-nine. The application of the slotted rotary wards, G G G G, or their equivalents, in combination with the driving pins, h h h h h h h h, and indicator L, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the driving ward gear, J, and driving bolt gear, O, or their equivalents, constructed substantially as specified.

Forty-nine. The application of the key, L, in combination with the ward and bolt gears, substantially as specified.

Forty-nine. The application of the slotted stud, substantially as specified.

paratus and a guide roller, R, essentially as described, combining the guide roller with it by means of a spring, or making the outer arm of the lever as a spring for the purpose of enabling such spring to operate the lever, in manner and under circumstances as set forth.

I also claim combining the inertial weight with the spring lever, so as to cause such to operate as specified, under sudden upheaval of the stern of the vessel.

FARE BOXES FOR OMNIBUSES, &c.—L. B. Slawson, of New Orleans, La.: I claim, first. The arrangement of an opening in the top of the fare box through which such coins pass, and which deposit their fare, when such opening communicates with a chamber in which such fare first falls, and is temporarily arrested previous to being deposited in the receiving drawer beneath, for the purposes set forth.

Second, I claim the arrangement of the passage block, D, and cover, E, over the opening in the fare box, for the purpose described.

CLASPS FOR HOOP SKIRTS.—A. Smart, of New York City: I do not claim to be the first inventor of hoop clasps, nor do I claim any part of the described clasp that is seen in the patent granted to T. Wallace, Jr., Jan. 15th, 1858.

But I claim, as an improved article of manufacture, a hoop clasp constructed with a longitudinal loop, e, substantially as and for the purposes shown and described.

CHURN—John E. Smith, of Galien, N. Y., and Wrightman Brown, of Rose, N. Y.: We do not claim as our invention an automatic churn.

But we claim the combination and arrangement of the cylinder divided into two chambers, for the purposes described, by the partition, M, the close interior case, R, adjustable vase blower and regulator, E, refrigerating passage, Y, and ventilators, v v, operating conjointly, as and for the purpose specified.

SEEDING MACHINES—Joseph D. Smith, of Lancaster, Ohio: I do not claim broadly the employment of two wheels for opening the furrow, the seed being dropped between the wheels.

But I claim the arrangement and combination of the sput, R, wheels, M, frame, H, and frame, D, as and for the purposes shown and described.

FEET WARMING DEVICE—George W. Smith, of Aurora, Ind.: I do not claim broadly, and irrespective of the arrangement and adaptation shown and described, the use of a steam chamber for heating purposes.

But I claim the employment or use of the chamber, I, when applied to a forge, and heated by steam generated within a box, E, or its equivalent, by the force of the forge, substantially as described.

CULTRAFONES—Nathaniel S. Smith, of Buffalo, N. Y.: I do not claim the fixed or hand cutting cylinder, B, nor placing a gang of hoes behind such a cylinder, nor the combination of the comb formed clearer with such a cylinder.

What I claim is the use of the double joint piece, D, to connect the gang of hoes to the axle, when said joint piece extends beyond the axle, and subserves also the purpose of a foot lever to throw the hoes out of the ground, in the manner and for the purpose set forth.

PROPELLER FOR BOATS—Le Grand C. St. John, of Buffalo, N. Y.: I claim, first, the construction and use of a propeller case having three conduits arranged on parallel lines, so that water may be received into the case through the outside conduits at the same stroke of the piston that water is discharged through the middle conduit, and vice versa, as set forth.

Second, I claim the arrangement of two revolving plates, E, E, with respect to an enclosing case, whether said case is made single, as represented in Fig. VII., No. 2, or double, as represented by No. 3, Fig. 1, and the combination thereof with a boat, so that in the act of propelling, water will be received into the case at one orifice or channel, and discharged at another orifice of channel, through the bottom of the boat, for the purpose substantially as set forth.

Third, I claim the construction of my revolving piston, partly of wood and partly of iron, substantially as described.

MACHINE FOR CUTTING IRREGULAR FORMS—Henry D. Stover, of Boston, Mass.: I claim, first. The guards, 3, and bar, L, carrying them combined with the revolving guide, G, in the manner described and for the purpose fully set forth.

Second, I claim the guide, G, so constructed and fitted to the outer surface of the bearing or tube, B, as to be vertically adjustable thereto to guide the pattern without wearing it, while the piece secured to the pattern relieves the shape from the cutting knives immediately above, essentially as set forth.

Third, I claim the combination of the adjustable elastic sleeve, L, with the tube or bearing, B, and guide, G, in the manner described and for the purpose fully set forth.

Fourth, I claim the slotted spindle, 4, collars, 6, and the cutter, constructed and relatively arranged and operated, in connection with each other, essentially in the manner and for the purposes fully set forth and described.

ROLLING RAILWAY CHAIRS—James H. Sweet, of Pittsburgh, Pa.: I am aware that the portion of the metal that forms the jaw or jaws has heretofore been raised up and then bent down into proper position. This injures the fibers of the iron and makes a bad chair. I do not claim any such method.

But I claim the process of rolling railroad chairs, the cutting under or into the solid iron for the purpose of forming the jaw, after the bar is rolled and bent, and thus avoid the raising up and afterwards bending down of the part that is to form the jaw, as heretofore done.

BRACELETS—Francis M. Sweet, of Syracuse, N. Y.: I do not claim the use of an elastic cord or band for the purpose of stringing loose pieces of jet or beads, as such are in common use.

But I claim the employment of the elastic rubber or spring connection between the two parts of the bracelet, operating substantially as described, and when the parts F and C are furnished with guides in the manner and for the purpose set forth.

HAT BODY MACHINERY—Alva B. Taylor, of Newark, N. J.: Having described my improvement, and a machine in which it is embodied, it may be proper to state that I do not intend to predict arrangement and construction described, but tend to those circumstances which render expedient. Thus for example, both disks of the picker may be caused to revolve either in the same directions with different speeds, or in opposite directions, and the picker may be combined with a perforated former not enclosed in a forming chamber, or with other devices than those described.

I claim the combination of a disk picker operating substantially as set forth, with a perforated former.

I also claim a picker composed of two disks, whose faces are studded with teeth, operating substantially as set forth, to pick fibers material fed into the eye of the picker, and to discharge the picked fiber at the run thereof.

GRAIN SEPARATORS—John D. Tift, of Cuyahoga, Ohio: I do not claim broadly the application of a valve to the fan case, nor do I claim broadly the employment of an adjustable apron or board.

But I claim the employment of a circular side valve, H, in combination with the directing board, J, when the parts are constructed and arranged as shown and described, for the purposes set forth.

TRAVELING CASE—T. R. Timbey, of Medina, N. Y.: I claim attaching the stiff sides, c c, of the traveling casket to the intermediate metal or other framing, d d, by means of rubber or other springs, B B, substantially as and for the purposes set forth.

Ox YOKES—George W. Weeks, of Boston, Mass.: I claim making ox bows and yokes, of iron or other suitable material, hollow, substantially as described, for the object specified.

WASHING MACHINE—Thomas J. Tindall, of New York City: I claim combining with a suitable vessel for containing the clothes, &c., to be washed, and the washing liquid, and the exhausting pump or equivalent therefor, communicating with the said vessel above the intended charge, substantially as described, to exhaust the said vessel above the charge and relieve the pressure, to effect the circulation of the washing liquid by ebullition below the recognized boiling point, as set forth.

ROLLING AND PILING LOGS—William Todd, of Cheshirefield, Me.: I claim the combination and arrangement of the tapered roller, E, with the diagonally arranged cylindrical rollers, A, for facilitating and guiding the movements of logs and heavy timbers, and piling the same in ranks or on teams and vessels, substantially as described.

APPARATUS FOR ROASTING COFFEE—Samuel Tower, of Grand Rapids, Mich.: I claim having a portion of each of the journals or axis, B C, attached to each sphere or shell, a b, and otherwise arranged and combined as set forth, so that when the spheres or shells are closed, the axis or journals will be completed, and the shells will be locked, all as and for the purposes set forth.

BRAKE—L. E. Truesdell, of Warren, Mass.: I claim, first, An iron bridge constructed with a series of vertical standard chords, C, in combination with vertical standards, B, and diagonal braces, A, or their equivalents, when the whole is arranged and connected together in the manner substantially as and for the purposes set forth.

Second, I claim constructing the clamp, D, in the manner and for the purposes substantially set forth.

SEEDING MACHINES—Alexander Turner, Redden Bass, and Harvey Sloan, of Franklin, Ind.: We wish to secure by Letters Patent the arrangement of the seed boxes, B and C, the seed slides, d and e, rod, H, wheels, G and F, and plows, J J, in the manner specified and for the purpose set forth.

SEEDING MACHINE—Joseph D. Smith, of Lancaster, Ohio: I do not claim broadly the employment of two wheels for opening the furrow, the seed being dropped between the wheels.

But I claim the arrangement and combination of the sput, R, wheels, M, frame, H, and frame, D, as and for the purposes shown and described.

STEAM WARMING DEVICE—George W. Smith, of Aurora, Ind.: I do not claim broadly, and irrespective of the arrangement and adaptation shown and described, the use of a steam chamber for heating purposes.

But I claim the employment or use of the chamber, I, when applied to a forge, and heated by steam generated within a box, E, or its equivalent, by the force of the forge, substantially as described.

ATTACHING THE PROPS OF CARRIAGE BOWS—D. B. Wright and L. Sawyer, of South Amherst, Mass.: We do not claim the employment of a movable shoulder piece which screws upon the prop, as in C. Thomas' patent.

But we claim as an improved article of manufacture, a carriage prop in which the prop, C, is rendered independent of its plate, B, substantially as and for the purposes set forth.

CORN PLANTERS—Franklin W. White, of Worcester, Mass.: I claim, first. Operating the seed slides through the rod, p, and its arm, r, and the hole or holes, s, in the wheel, d, substantially as described.

I also claim, in combination with a dropping apparatus, and the double mold boards for opening the furrow, the openings, w, and guides, x, for admitting and directing the earth or soil that is to cover the seed, substantially as described.

TEASE FASTENING—John C. De Witt, of West Bloomfield, N. J., assignor to himself, and Turah Benedict, of Newark, N. J.: I am aware that buckles have been formed with tongues so arranged as to pass through the perforations of traces at right angles, and I therefore do not claim broadly such device.

But I claim the frame or body, D, provided with the tongue, t, projecting from it at right angles, when the frame or body is connected with the plates, e, of the tug, A, by means of the pivots, b b, of said plate, fitting in oblong slots, c, in the slides, d d, of the frame or body, so that in the same manner it is shoved forward and backward to admit of its being locked, and also of being opened, substantially as described.

INKSTAND—V. Fogerty, of Cambridgeport, Mass., assignor to Francis Houghton, of Somerville, Mass.: I claim, in combination with an inkstand or ink-reservoir, and its mouth, a dipper or vessel so applied with respect to the cap of being within it, and having the cap as the receptacle for the ink, substantially as described.

I also claim the application of the dipper to the movable cap of the mouth of the reservoir, so as to be operated by the said cap, in manner substantially as explained.

KNITTING MACHINES—Thomas Lovelidge (assignor to himself and William Tuftith), of Germantown, Pa.: I claim the pressure plate, E, situated between the two rows of thread guides, d and d', and operated so as to press the loops down the needles, substantially as for the purpose set forth.

SEED PLANTERS—W. A. Mahaffy, of Carimona, Minn., assignor to John Greek, of Evansville, Ind.: I am aware that the reciprocating perforated seed slides have been constructed, and I am also aware that wheels or cylinders provided with seed cells have also been used for distributing seed, but I claim the reciprocating slides have been used in connection with rotating cylinders, provided with seed cells and pins to serve as cams or triggers to actuate the slides, and also as conveyors to carry the seed to the conveying tubes. I do not claim, therefore, separately and broadly, the seed slides, nor the wheels provided with seed cells.

But I claim the seed slides, b, in combination with the wheels or cylinders, E, arranged for joint action, substantially as and for the purpose set forth.

REGULATING THE TENSION OF THE THREAD IN SEWING MACHINES—John T. H. Rogers, of New York City, assignor to George B. Sloot, of Philadelphia, Pa.: I do not claim regulating the tension of the thread by graduated friction thereon, or by causing it to pass over variable angular surfaces.

But I claim the combination, substantially as shown and described, of the cone, A, and conical cap, B, for the purposes set forth.

CUT-OFF FOR STEAM ENGINES—Jacob Windmer (assignor to himself, and Howard Gilbert), of New Haven, Conn.: I am aware that many regulators and cut-offs for the steam engine have been known and used, some of which have been regulated by the pressure of the steam. I therefore do not claim regulating the uniformity of the motion of the piston by the pressure of the steam, as my invention.

But I claim the combination of the bevel gear pinion, J, operated by the endless chain, L, and rod, M, with the bevel gear wheel, H, with its cam, G, when the whole is constructed, arranged and made to produce the result substantially as described.

ICE-ISSUES—

HARVESTERS—W. H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of the vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

whether the devices employed to effect these movements be such as described, or others equivalent thereto.

Fourth, The method of holding a sweep rake firmly, while raking the grain with the points of its teeth, in the proper position relative to the platform, by means of a lateral or other equivalent thereto, which operating with a greater certainty than a weight, spring, or other fastening not rigid, more effectively prevents the rake teeth from rising to override the grain, and at the same time avoids the necessity of moving a heavy weight, or of overcoming the tension of a strong spring, in elevating the rake preparatory to its retrograde stroke.

Fifth, The construction and arrangement of a sweep rake and the mechanism for operating it, in such manner that it is carried back and forth, and its teeth raised and lowered, without stopping the platform.

Sixth, Changing the frequency of the alternation of the raking mechanism, by means of the shifting gear or other equivalent device, for producing a varying rate of motion for the purpose of varying the size of the sheaves as may be required, substantially as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of the vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of said platform, as set forth.

HARVESTERS—William H. Seymour and D. S. Morgan, of Brockport, N. Y., assignees of N. Platt, formerly of Ottawa, Ill.: Dated June 12, 1849; reissued May 23, 1854; re-released August 31, 1858: What is claimed under this patent as the invention of the said Nelson Platt, is the combination of a vibrating sweep rake with the lever carrying the same, vibrated by gearing located within the inner edge or circle of

New Inventions.

Improvement in Electrotyping.

The National Intelligencer says an improvement in the process of electrotyping has been made, by which electrotypes can be produced with great rapidity and accuracy. The improvement consists in covering the face of the wax or other material of which the matrix is made, with fine metallic leaf before the impression is taken. In this way a perfect conducting metallic surface is obtained; that is, over the entire face of the letters, as well as over the spaces between the lines.

The sides of the letters do not, as a general thing, have a metallic conducting surface, inasmuch as the type, when the impression is taken, cut the leaf, and force a part of it down into the matrix, thus leaving the wax exposed on the sides of the letters. This cutting of the leaf, however, is rather an advantage, since such exposed parts of the wax are the very parts where a slow deposit is preferred, and which is effected by touching such parts over with plumbago. The advantages are these:—The moment that the mold or matrix is placed in the bath and the battery applied, the deposit of metal commences at once on the entire surface—the deposit being more rapid, however, on the face of the letters and on the spaces between the lines than on the sides of the letters; and this is just what is wanted, since it prevents, especially when the letters are small and deep, what is termed "bridging over" (hollow letters). By the use of silver leaf an electrotype may be produced with a bright silvered face—a feature of considerable importance in all cases where the plates are to be laid aside for future use, inasmuch as the face of the letters will not be so easily injured by long and continued exposure to air and moisture, as when of the usual copper face.

Electric Illumination.

Some attempts recently made at Paris towards illuminating the bottom beneath water, possess considerable interest in a scientific point of view. The electrodes of carbon were placed in a glass globe, being connected with one of Dubosq's regulators, which communicated with the battery by a copper wire covered with gutta percha. The globe submerged to a depth of fifteen feet, spread light over a circumference of thirty feet radius, and it remained constant for two hours, after which the carbon required replacing. Dubosq's arrangement is light, so that a submarine diver may carry it in his hand, and at the same time it is strong and well secured hermetically to resist a pressure of six hundred pounds of sea water. It consists of a cylinder of strong glass, secured to a brass foot, and surrounded with a gutta percha sack. The light passes out through a large plano-convex lens, with the convexity inward, the focus being so arranged that the rays escape nearly parallel. As the lamp is movable, the diver walks about with it, and places it in the proper relation to the point where he wishes to make any search; and as it is only necessary to bring the electrodes near one another to light it, the diver need only turn a small screw to continue the light for two hours, which is more than twice as long as he can remain at the bottom.

Improved Hop and Hay Press.

When, as often happens in presses, the follower in its descent takes an inclined position, the press will not of course operate with freedom, but in the subject of our illustration this difficulty is the subject of special attention, and has been successfully overcome.

The accompanying engraving is a perspective view of the hops, hay or cotton press, invented by Lincoln L. Cummings, of Munnsville, Madison county, N. Y., and patented by him June 15, 1858.

A represents a case or box of rectangular

form, in which is fitted a follower or plunger, capable of working freely up and down. C is a bar that is placed on the top of the follower and longitudinally with it, the ends of the bar projecting beyond the ends of the follower, and having a T-shaped slot, a, made vertically in each end. On each end of the bar, C, a cap, D, is placed, having oblong slots made through them. These caps are provided at each end with a handle, c, and on each cap a plate, E is placed, passing between guides, d, which form part of the cap, D.

The plates are adjusted by crank handles, F, and screws, e, which pass through a central opening in E.

To the bottom of the case or box, A, a bar, G, is attached. This bar projects beyond the box at each end, and to it a chain, H, is attached. To the upper end of the chain a screw, I, is secured, and these screws pass through the inner part of the slots, a, in the bar, c, through the slots in D, through E, and a nut is fitted on to each screw above the plate, E. Each nut is surrounded by teeth,

brace by means of a crossbar for the handles, C. To the back part of A, a wheel, D, is secured to support the back of the machine. E is a seed box, supported by bars, e, and a seed or discharging tube, F, the lower end of which is connected with a tube, G, secured to the underside of the frame, and having a furrow share, H, formed on its lower end. In the upper part of the tube, F, a slide, I, is placed, and a slide, J, is placed in the lower part of the tube, G. These slides work through the backs of the tubes, and are connected one to the upper, and the other to the lower end of rod, K, which is pivoted in the frame, A. To the upper end of the rod, K, a rod, L, is pivoted, the latter rod working in a guide in the bottom of the seed box. The outer end of the rod, L, is bent upwards, and is fitted in a groove in the slide, M, which works in the bottom of the seed box. N is a rod that is attached to M, and to the arm, O, of the crossbar, B, to which it is also attached another arm at right angles to the first. This is connected by the link, Q, which is also connected with a projection from the tube, S, that is fitted loosely upon one of the handles. The slide, M, has an oblong longitudinal slot made in it, and an adjustable plate or slide is fitted in this slot, the slide being adjusted by a set screw. By adjusting the plate the slot may be made of greater or less capacity as occasion may require. In the front end of the feed box, E, a vertical slide, T, is placed; this is provided with a brush or cut-off, and is regulated by the set screw, q, and this prevents the slot becoming piled up with seed and holding more than its proper quantity.

The operation of the machine is simple. The seed to be planted is placed on the box, E, and the slot in M regulated to contain the proper quantity, then as the machine is drawn along the ground the operator with his right hand turns S half round, first one way and then the other, and by so doing moves the slides, M I J, so that the seed can be stayed from falling, or permitted to fall in exactly the place required. The covers, U, then throw soil over it, and D aids in pressing it lightly down.


A patent was granted for this invention June 22, 1858, and any further information can be obtained by addressing as above.

Vehicles of Intelligence.

Newspapers, like nations, have a historical existence. They "go to and fro" in the avenues of society and exert a powerful influence. Tribes and individuals far removed from hearing what is transpiring among men are always ignorant and degraded. That person who uses means to obtain record of passing events always improves and advances in knowledge; the man who is dead to such influences is dead to his own best interests. Well did the old Greeks know the value of obtaining new information. When voyagers and travelers came to their ports and cities, they were taken to their public marts and requested to recite an account of what they had seen and heard abroad. The influence of this custom, before the art of printing was discovered, was like that of our modern newspaper; it tended to excite the people, and lead them to achieve reputation in all that was held worthy of being distinguished. The result was, they attained to the loftiest position in learning and the arts in those days, and in many things they are still our masters and instructors.

As attainments in the useful arts make men distinguished and nations great, we take occasion at the commencement of a new volume to solicit the favor of our constant readers in extending the circulation of a paper devoted to disseminating such information among the people as is useful and elevating. We urge our friends to give us their assistance in presenting the claims of the SCIENTIFIC AMERICAN to their acquaintances. We have no doubt but there are a great many mechanics, manufacturers, and others, who would become subscribers were our paper brought to their notice, and its character and advantages pointed out by those who know it well.

CUMMING'S HOP AND HAY PRESS.



g, into which a spring pawl, K, catches. These pawls are fitted in sockets, L, that can move freely upon the nuts. In these sockets, L, hand levers, M, are placed, to operate the press.


Each side of the case or box, A, at its upper part is formed of a series of slats, h, which are placed one over the other between proper guides, so that they may be withdrawn as the follower descends, and the substance within the box is compressed.

The operation is as follows:—The follower is depressed upon the hops, hay or cotton by

turning the hand levers, M, and consequently the nuts, so that as they are made to descend on the screws, I, they carry C and the follower with them. Should the follower become inclined, as the screws, I, have room to move in the T-shaped slot, a, so that it will operate the follower when inclined, and gradually make it level.

Many of these presses are in use for hop pressing, and give general satisfaction. They are for sale by the inventor and manufacturer, and any information concerning rights, &c., can be obtained by addressing him as above.

JONES' SEED PLANTER.



The object of the inventor of this seed planter—S. F. Jones, of St. Paul, Ind.—has been to furnish one in which the operator would have a full and perfect control over the distributing device, without regard to the draught movement of the machine, so that he could deposit the seed at the precise spot desired. That this object has been fully at-

tained will be seen from the following description and accompanying engraving, which is a perspective view of this seed planter.

A is the frame composed of two parallel bars to the front ends of which the tongue, B, is secured. The back ends of the bars are connected by a bar, d, to the center of which an upright, c, is attached, which serves as a

Scientific American.

NEW YORK, SEPTEMBER 11, 1858.

The Great Celebration and the Atlantic Telegraph.

Our whole country, from its circumference to the center, has been electrified by the successful laying of the Atlantic Telegraph—that instantaneous highway of thought between the Old and New Worlds. It was an enterprise in regard to which all men wished for success and certainty. Great honor is due to those who devised and organized the project, and conducted its operations. The indomitable perseverance which they exhibited under so many difficulties and embarrassments of an adverse character, and their final triumph over all these, deserve the highest praise. The names of the most prominent of these parties—Field, Morse, Everett, Bright, Hudson, and others—have been held up before our people with marked respect. But perhaps the grandest feature in the whole affair was the spectacle of the two greatest nautical and Christian nations in the world employing their resources, and noblest vessels of war, in carrying out this gigantic scientific and commercial undertaking. We hope it may be an augury that war shall hereafter be unknown between them, and that in future their rivalry shall be "mutual co-operation to advance arts, commerce, and science."

Wednesday of last week was set apart as a day of public rejoicing in New York for the success attained in laying the cable, and we never witnessed on any previous occasion such a grand and universal demonstration. All classes, orders and societies turned out in procession to offer testimony to the feelings generally entertained towards those who were engaged in the accomplishment of the triumphant event. The officers of the frigate *Niagara* and those of the British war steamer *Gorgon* were received in style by the city authorities.

Te Deum was executed in Trinity Church in honor of the occasion. Titled lords, prelates and priests graced the spectacle. Magistrates from distant cities, and soldiers from Canada took part in the services. The crowning arch in the grand cavalcade, however, was the appearance of the Industrial trades. Printers, coopers, millers, carpenters, machinists were there each exhibiting their varied arts as the columns moved onward towards the Crystal Palace, where, in the presence of ten thousand people, David Dudley Field, Esq., pronounced an oration. It was a most happy sight to see that venerable inventor, preacher and scholar, Dr. Nott, enjoying peaceful communication with his Grace the Archbishop Hughes, thus exhibiting a most agreeable illustration of the spirit of "peace on earth and good will among men," such as is the promise of good things to come.

In the evening, there was a brilliant illumination and a gorgeous torchlight procession by the firemen, and, on the whole, no such display has been witnessed here since the first Hollander set his foot on Manhattan Island. The circumstances undoubtedly warranted some such exhibition of public feeling, although its keen relish was somewhat blunted in the estimation of many good men when they remembered the fact that it was got up and managed by a mass of swindling officials, who will in some manner make the taxpayers smart for the cotton, paint, liquor and cigars supplied on the occasion at their expense. We can somehow overlook the heartless part of the exhibition, when we consider this ovation as an acknowledgement due to that power of science which has enabled man to hold converse with his fellow man through the depths of the great sea, through that path spoken of by Job, "which no fowl knoweth, and which the vulture's eye hath not seen; the lion's whelps have not trodden it, nor the fierce lion passed by it."

In regard to the operations of the enterprise, many superficial and incorrect statements have been put forth by various publications. No new invention of any great consequence was involved in laying the cable. Submarine cables had been laid before, but they were on a much smaller scale. The achievement derives its importance from its greatness, as being the most gigantic effort ever made to extend telegraphic communications between distant continents. Whether the Atlantic Cable will ever realize all that has been expected from it by sanguine persons remains to be demonstrated—thus far it has not. Its operations have, as yet, been of a very puzzling and tedious character. On page 184, Vol. XII., SCIENTIFIC AMERICAN, the nature of the submarine cable as an electrical conductor was explained. It was there stated to be a vast Leyden jar, and messages could not but travel very slow in it—requiring about six seconds for each signal, and therefore incapable of transmitting more than about half a column of news in twenty-four hours. As yet it has not come up to this figure; and it has baffled all efforts to work successfully any of our common telegraphic instruments. The messages sent have been by slow "time signals," and many very incorrect and contradictory statements have been put forth by those interested, which are calculated to mislead the public. Thus in the published statement of G. Saward, manager of the line in England, he asserts that the Queen's message to the President, consisting of ninety-nine words, was received in Newfoundland in sixty-seven seconds; whereas we know, by the published statement of M^r. de Santy, manager at Newfoundland, it took about twenty-four hours. All the messages—and they are but few in number—which have been sent, have required a very long time in their transmission. With the very best known instruments messages will be very slow, and unless some new discovery is made to remove existing obstacles, the Atlantic Telegraph will be of very little general benefit to the commercial people of the two continents. It will undoubtedly be a great national benefit for special purposes, but that will not meet the wants of the public. The instruments for operating the cable ought to have been adjusted and in working order long ago. That this has not been done affords reasonable grounds for concluding that greater difficulties have been experienced than were expected.

Relation of Masters and Apprentices.

We have often thought that if masters properly comprehended the relation they sustain to their apprentices and employees, their pecuniary interest would not only be greatly enhanced, but that a positive good would be rendered to every branch of industry in which they are engaged, as well through a more harmonious concert of action as a superior social elevation given to the worthy class under them. To our view, this relation is somewhat analogous to that existing between parents and children, so far as the development of their minds and the instilment of sound principles of morality and industry, the encouragement of skill in manipulation, and the attainment of knowledge are concerned. We believe the observation of a celebrated master, that no one is born without capacity for some branch of industry, is a just one, and that where stupidity exists it is nothing else but neglect of proper discipline and education in the youth of the person thus unfortunately deficient. To establish this fact it needs no fresh arguments of ours to show how extremely ductile, how capable of government and restraint, and how susceptible of instruction human nature is, when approached in the proper spirit of kindness, dignity and respect, which stimulates zeal and ambition, and produces a corresponding return.

The first duty of a master should be to present in himself an example for imitation in the elements of industry, morality, system, and the other attributes which constitute a

superior mechanic or workman. There are many apprentices who have so much of the spirit of self-reliance and genius that this example is not essentially necessary; but if we pursue the reflection, and for the certainty of the rule consider (what no man can fail to observe) the effect the characters of others of a superior rank have upon those immediately connected with them, it will be obvious to all that the master, in a great measure, impresses the inferior with the prominent traits of his character. They should, moreover, observe and study the dispositions and minds of their apprentices, with a view of conciliating their regard and confidence, and through this means to establish a free and familiar intercourse, and render the task of instruction and development more simple and easy. As the apprentices advance in knowledge and skill, suitable evidences of appreciation and encouragement should be given them. This will stimulate their ambition and exertion, and create among them a worthy spirit of emulation.

Where the character of an apprentice is such as to require a tight rein upon his actions, and the deprivation of privileges, and other suitable punishments for idleness and misconduct, care should be observed that these curbs and punishments do not descend into such acts of tyranny as will destroy the spirit and ambition of the youth, and render him obstinate, unruly, and beyond all future influences of excellence and good. Besides a thorough instruction in his trade or profession, and a sound and healthy education to otherwise render him fit for his social position in life, it should be the aim of a master to instil into his pupil all the scientific and other knowledge possible, even should such knowledge have no direct bearing upon the business or trade in which he is engaged. Such acts of interest, kindness, and confidence as these, and others of a corresponding character, cannot fail to produce the most marked beneficial results upon the interests of the master, and the happiness and condition of the grateful apprentice.

The Yellow Fever.

Some time ago we remonstrated strongly against the course of Dr. Thompson and the Board of Health of this city, for the careless manner in which infected ships were treated by them, and this journal was the first to call the public attention to their official stupidity in allowing the U. S. ship *Susquehanna* to remain for three months in the cool weather, without attempting to do anything for her restoration to usefulness, and then when the thermometer got to "fever heat," they busily stirred themselves to get her disinfected, by risking the lives of stevedores and others, in a reckless and unnecessary manner. Since that time, many other infected ships have been treated in the same way, and at this moment there are too many opposite the Quarantine station, which is only six miles from the city. The consequence of this careless conduct is that yellow fever has broken out in three distinct parts of Staten Island.

Since writing the above, the whole of the Quarantine buildings have been burned to the ground by a mob, and the sick left uncared for. The doctors deserve the credit of having stuck to their posts like brave men during the whole of the conflagration. We hope that the perpetrators of the wrong may be apprehended and punished, for it is no way to redress one evil to allow a ruffianly gang to take the law into their own hands.

RECOVERY OF ELECTRIC CABLES.—The two electric cables which Mr. Brett endeavored in vain, about two years ago, to lay down between Spartiventi, Borea and Gallita, have, according to *Galigiani's Messenger*, been discovered, and taken on board an English steamer, which arrived at Elba a few weeks ago. From a casual observation, it appeared to be but slightly affected by abrasion and other causes to which it was subjected during its long residence in the mystic deep.

The Progress of Invention.

It is with pleasure that we commence this new volume with such a fine list of patents, issued during the past week; and we can congratulate the inventors of the country that gradually their noble mission is becoming appreciated, as is evidenced by the tribute now so generally bestowed upon those men of genius who have been engaged in laying the Ocean Cable. Perhaps no better evidence of the increasing interest felt in invention and the growing genius of our country can be found in the records of the Patent Office. We can state two facts which will show the rapid progress that has been made. During the year encompassed by Vol. XII of the SCIENTIFIC AMERICAN, 426 patents were issued to persons who had made their applications through our Agency, while in the year just closed, embraced within Vol. XIII, 888 patents were issued to our clients!

Making a selection from the List of Claims published in this first number of Vol. XIV., we find AGRICULTURE well represented, and we will proceed to give some idea of the new inventions in this class. In fact, the cultivation of the earth, and the production of machines which facilitate the tilling of the soil, and the gathering of its fruits, are the subjects which, more than any other, engage the inventor's attention.

John D. Fifts, of Cuyahoga Falls, Ohio, has invented an improvement in separators or winnowers. It consists in having the discharge orifice of the fan case provided with a segment shell, by which the size of the orifice may be regulated as occasion may require, and using in connection with the slide an adjustable blast director, so that the device is well adapted to winnow large or small grain.

L. H. Parson and G. Houston, of Middle-town, N. Y., have invented an improvement in the wire-toothed horse rake. They employ supplemental springs, arranged and connected with the teeth, so that while the teeth are properly braced and stayed, they have at the same time the requisite degree of elasticity.

Next comes an improved clearing device, to be applied to seed drills, invented by O. H. S. Brumfield, of Centerville, Ind. The invention consists in having a series of hooks or curved teeth attached to a rod, the ends of which are fitted in horizontal guides, and connected to pitmen, which are attached to cranks, these parts being so arranged as to clear all weeds and other obstructions from the ground in advance of the drill, and thus prevent its clogging.

Messrs. Coullin & Newton, of Stirling, Ill., have produced a novel seed-distributing device, especially applicable to broadcast seed planters.

J. B. McCormick, of Versailles, Ky., and W. R. Baker, of Boston, Mass., have invented an improvement in seeding machines, which relates to a novel means employed for forming the drills or furrows, and dropping the seed into the ground.

The next invention, that of E. L. Lyon, of East Randolph, N. Y., relates to an improvement in that class of seeding machines in which the seed-distributing devices are attached to the wheels, and are operated by the rotation of the wheels as the machine is drawn along. The invention consists in the peculiar construction and arrangement of the distributing devices as applied to the wheels, so that seed may be planted evenly either in check rows or in parallel drills.

Joseph D. Smith, of Lancaster, Ohio, has also invented a machine for planting maize, or corn, and other seed, in check rows. The invention consists in a peculiar seed-distributing device, and also in a novel device for forming the necessary furrows to receive the seed also in a peculiar arrangement of the framing, whereby the device is allowed to conform to the inequalities of the ground, and the seed-distributing portion elevated free from the ground, when desired, or when mov-

Scientific American.

ing from place to place, or in turning at the ends of rows, &c.

And last, but not least, W. A. Mahaffy, of Carimona, Minn., has made an improvement in the seed-distributing device of seeding machines, whereby the seed is discharged in measured quantities from the seed box, and conveyed from thence to the conveying tubes at the bottom of which the furrow teeth are formed, the seed being deposited in the furrows in quantities precisely the same as they are discharged from the seed box.

In STEAM apparatus and appliances we notice the steam cock invented by Albert Fuller, of Cincinnati, Ohio, which is composed of a plug of rubber or other suitable elastic material, placed on the valve stem, and fitted between a metallic shield on one side and a metallic cap on the other, the cap having a nut bearing against it. By these means due provision is made to compensate for the wearing of the plug, and the casualty of the forcing of the plug through the valve seat by the pressure of the steam effectually guarded against.

J. H. Winn, of Portage, Wis., has invented an improved apparatus constituting a combined safety valve and steam pressure gage, which consists in a very simple method of applying and arranging one or more weighted pendulous rods, and an index and dial in combination with a piston valve and suitable arrangement of steam passages, whereby the escape of steam from a boiler, as soon as it arrives at any desired pressure, is provided for, and any pressure of steam below that at which it is desired to escape, is correctly indicated by the index on the dial.

Travelers, emigrants, and in fact every one who ever has had to travel in a railway train by night, and who knows the uncomfortable ness of a night journey—how the cars rocked, but allowed no sleep—how you tried to make yourself comfortable, and could not—all who have experienced the inconvenience will thank J. C. Dewitt, of West Bloomfield, N. J., K. Freeman, of Fond du Lac, Wis., and W. Painter, of Wilmington, Del., because each of these inventors has invented a method of arranging seats, and other parts of railway cars, so that without taking away any often necessary room in daytime, they can in a few moments be made into sleeping cars, giving a good bed or berth to as many as were seated. We cannot explain them without engravings, but each has some special feature to commend it to a favorable reception by the railroad companies and traveling public.

Among those inventions which may be said to promote DOMESTIC ECONOMY we see many useful improvements. First we may notice the lamp invented by James P. and Ellen Kenyon, of Brooklyn, N. Y. It is especially adapted for burning coal oils or other hydrocarbons, and as these contain variable quantities (according to their purity) of carbon and hydrogen, they require a greater or less supply of air to the flame. To obtain this exact quantity with little trouble, two wicks in separate collapsible wick tubes are employed, and placed at such an angle that their flames meet and join together, while between them a current of air is supplied to support combustion. Outside these wick tubes is a cap or cover, by raising which the wick tubes separate, and consequently more air passes up to feed the flame, and by depressing the cap they are brought closer together, and less air passes up between them. By lighting the lamp and moving this cap up and down, any one can regulate the amount of air which will fully consume the particular quality of oil then in the lamp, and consequently there is no smoke, and no necessity for a chimney, or any artificial draft creator.

G. W. Smith, of Aurora, Ind., has invented a foot-warmer for forges, which is a chamber or box placed in the ground, or below the flooring adjoining the forge, and the place where the workman usually stands. This box is supplied with steam generated in a water heater, if such be used, or if not, a tank

is inserted in the wall of the forge, so that steam may be generated in it, and supplied to the foot-warmer.

J. H. Roome, of New York, has made an improvement in tailors' and other shears, by forming the handle and upper cutting blade of the shears in two parts, and so connecting the former to the body or shank of the lower cutting blade and to the upper one as to enable the leverage exerted by the thumb to be gradually increased with the closing of the blades.

A. W. Hale, of New Britain, Conn., has invented an improvement in portable pressure bells for house use. It consists in the employment of a vertical sliding arbor, which works through the center of the shell of the bell, said arbor having a pin projecting horizontally from it, and also having a spiral spring placed around it, the above parts being used in connection with a spring or elastic tongue, provided with a projecting plate, so that a very simple device is obtained for sounding the bell by simply depressing the arbor.

A simple, cheap, and efficient coffee-roaster has been invented by Samuel Tower, of Grand Rapids, Mich. It is simply two hollow hemispheres of metal, which, fitting together, form a spheroidal or spherical chamber, in which the coffee is placed to be roasted. The axle on which it is rotated forms a lock to keep the two parts together, and it is equally applicable for household or manufacturers use.

The ladies have lately given much employment to inventive genius, and the ingenuity of many inventors has expanded in direct proportion with the size of those much abused, but graceful additions to the female form—the hoops. A. Smart, of New York, has invented an improved metallic clasp for securing the hoops to the tapes of skeleton skirts. This clasp is a small plate of metal secured to the hoop, and the tape passes through slits in the back, and is there held secure. It is simple and convenient, doing away with all knots, and other annoyances.

A. G. Davis, of Watertown, Conn., has invented a new parasol and sun umbrella. The invention consists in having the handle of the parasol, sun shade, or sun umbrella formed of two parts, one part being fitted into and allowed to slide in and out from the other, and used in connection with a stop and pressure bar, slide ferrule, and hub, the whole being arranged so that the handle may be extended or lengthened as the implement is opened, and shortened as it is closed or folded.

J. T. B. Rogers, of New York (assignor to G. B. Sloat, of Philadelphia, Pa.), has invented a new device for producing tension on the needle thread of sewing machines. The invention consists of two conical surfaces, one of which is concave, and forms a cap to the other, which is convex, and an adjusting screw and spring, the whole being combined to produce upon the thread passing between the cones, friction, which is sufficiently variable to produce a degree of tension on the thread that can be regulated with extreme delicacy.

John Agnew, of Columbia, S. C., has invented an improved coupling for securing together the ends of metal bale hoops, which consists in having a small metal casting with a longitudinal slit in it, of double taper form, and having the ends of the hoops doubled, or bent over in loop form, so that the same may bind or become wedged in the casting, forming a perfect fastening.

William Todd, of Cherryfield, Me., has invented a combination of rollers, placed at such an obtuse angle with each other, and a tapering roller placed beside them, so that pieces of lumber may be rolled on to them and guided to the tapering roller without regard to the position of the loop. It is intended to facilitate the piling, removal or stowage of logs or lumber.

Isachar A. Hansell, of Springfield, Ill., has produced a drawing-board for perspective drawing. It has an adjustable curved strip fitted in each side of the board, the outer

edges of the strips being curved parts and forming guides for the square, the curves being struck or formed from the vanishing point or points of distance of the object to be drawn, and determining the proper angle at any point of their curved surface for the vanishing lines. The board has also straight guides at each side in order that the square, when required, may be adjusted parallel with the base of the board.

Jeremiah Howard, of New York, has made an improvement in mills for crushing sugar-cane, which consists in applying, by suitable means, hydraulic pressure to the lower roller of a crushing mill, so that the rollers will be allowed to yield or give, and the space between them and the upper rollers be regulated according to the work to be performed.

An invention which has long been wanted, is supplied by A. Pearsall, of Nashville, Tenn., who employs an inclined mandrel, clamps and welding roller, arranged so that in the machine, bellows' pipes and nozzles may be closed and welded in a very expeditious and perfect manner.

The carding machine has received some improvement from C. E. Price and J. Haythorn, of Thompsonville, Conn. The invention consists in the employment of a revolving spirally-grooved or threaded cylinder, applied below the comb which removes the fleece from the doffer, and near to and parallel with the doffer, for the purpose of receiving the fleece as it is struck from the doffer by the comb, and conveying the same away by means of its revolution, in a direction parallel with the axis of the doffer, through a tube arranged at one side of the machine. By this contrivance they are enabled to produce a better quality of yarn from stock of given quality, and make very little waste.

In making carriages more comfortable, and providing for the safety of persons who take the easy exercise of carriage riding, we notice two inventions. The first is a carriage bow prop invented by D. B. Wright and L. Sawyer, of Amesburg, Mass., the object of which is to obviate the difficulty attending the present mode of attaching props to carriage bows. By the present mode of attachment the leather or covering of the top is not allowed to work or move around the prop, and consequently it is liable to wrinkle, as the braces or rods which the props support are moved, and the top raised and lowered. The usual strain, also, to which the leather is subjected, is avoided, and the improvement makes a better finish, adding considerably to the appearance of calash tops, and also allows mechanics better facilities for finishing or "binding off" the top.

John C. Dewitt, of West Bloomfield, N. J., has invented a new buckle for securing harness traces and hame tugs, the object of which is to obtain a buckle or fastening for securing the traces of harnesses to their hame tugs without injuring the traces as is the case with the ordinary buckle, and at the same time to obtain also a fastening that will admit of a ready adjustment and form a sure connection.

Here we must stop, and yet there are many other valuable inventions in this week's List of Claims which we must, from want of space, omit to notice, but we have at any rate shown a sufficient number to demonstrate the wide range that invention takes, and to prove the progress of mechanical science.

PUBLIC FOUNTAINS.—The citizens of Birmingham, Eng., not having spent all the money which they appropriated for the reception of Queen Victoria in their city, have devoted the surplus to the erection of public fountains. Why cannot all our cities imitate Philadelphia, Liverpool, Paris and other cities, in this, and provide plenty of fountains, to gush forth cooling water, to cheer and improve the thirsty, weary inhabitants. We are forcibly impressed with the statement that the money appropriated was not all expended. No such libel as this has ever been charged against the managers of similar affairs in this city.



* Persons who write to us, expecting replies through this column, and those who may desire to make contributions to it of brief interesting facts, must always observe the strict rule, viz., to furnish their names, otherwise we cannot place confidence in their communications.

MULTUM IN PARVO.—In 1630, David Ramseye, the King's Poet, took out a patent in England, No. 53, embracing the following points:—First, To multiply and make saltpetre in an open field, in four acres of ground, sufficient to serve in his Majesty's dominions. Second, To raise water from low pits by fire. Third, To make any sorts of mills to go on standing water by continual motion, without the help of winds, weight or horse. Fourth, To make all sorts of tapestry without any weaving loom or way ever yet in use in this kingdom. Fifth, To make boats, ships and barges go against wind and tide. Sixth, To make the earth fertile more than usual. Seventh, To raise water in a new way. Eighth, To make hard from soft and copper to be tough and soft, and to make yellow wax white very speedily.

W. W. H. of Texas.—The conical ball, with the charge in a hollow at the rear, as described in the New Orleans *Delta* as a Russian improvement, is not new. Such balls have been used in the United States.

TUBULAR AIR RAILWAY.—S. T., of Philadelphia, inquires: "Was there not a patent issued a few years since for the transmission of mails through pipes by atmospheric pressure? Has it been abandoned, or is the inventor still sanguine of success?" The idea referred to for carrying mails is old, but a patent was issued a few years since for an improved mode of accomplishing the object. The invention was illustrated and described on page 265, Vol. VIII, Sci. Am. We believe the inventor—I. S. Richardson, of Boston,—is still sanguine of success.

ALL ABOUT A SNUFF BOX.—The original inventor of the Ayreshire snuff boxes, so well-known in Great Britain, was a cripple, hardly possessing the power of locomotion. They are made of wood, admirably joined, painted and varnished, and were first manufactured about sixty years since. Instead of taking out a patent, the inventor intrusted his secret to a joiner in the village, who in a few years amassed a great fortune, while the other died as he had lived, in the greatest poverty. Speaking of snuff-boxes, snuff-taking took its rise in England in 1702.

CURIOSITY.—The popular belief that young birds are assisted in escaping from the shell by the parent, is refuted by a talented author. The beak of the chicken is tipped with a bony point; this is protruded through the shell, and afterwards drops off. By means of its feet as levers, the animal turns itself little by little, till by degrees the whole top of the large end of the egg is cut cleanly off, and thus the prisoner is set free.

J. C. S. of Mass.—Your communication of the 28th ult. is placed among our private files. If you go on at this rate there will soon be nothing remaining undiscovered in the projectiles for efficient manslaughter.

T. M. of Va.—Messrs. Phelps, Dodge & Co., of this city, are extensive importers and dealers in tin plate. This firm is very reliable, and you can safely remit money to them.

A. H. G. of Vt.—If a straw cutter, a washing machine, a saw, a coffee mill, &c., are all arranged to be operated by a single shaft, such combination could not be patented. Each of these machines would fulfill its appropriate function independently of the other, therefore there is no proper combination. To make the matter plain, the coffee mill could do its grinding without the aid of the washing machine.

TELEGRAPH.—A Philadelphia correspondent inquires if Franklin did not invent the first electric telegraph, "he having sent an electric current through the Schuylkill river, and made signals in 1748, thus demonstrating that electric messages could be sent great distances nearly a hundred years before Professor Morse invented his telegraph (1839)." Franklin accomplished the result mentioned by our correspondent, but a like effect had been produced in 1739 by Messrs. Wheeler and Grey, in England. The electricity which they employed was frictional, and could not be successfully applied to public telegraphing. Voltaic electricity was not then discovered. The application of electricity to telegraphing was essayed by various persons long before Professor Morse invented his telegraph; but his invention is entirely different from all his predecessors. He did for the telegraph what Watt did for the steam engine, and he put up the first really successful line of public telegraph (in 1844) in our country.

CLOCKS.—A correspondent in Cincinnati inquires: "where were clocks first made in America; and how have Yankee clocks gained such a world-wide reputation?" We cannot answer the first question positively, but clocks were manufactured at a very early date in Hartford and Litchfield, Conn. A patent was granted to Benjamin Hanks, of Litchfield, in 1788, for a self-winding clock, and at that period the wooden time-pieces of New England had acquired a high character. Their works were made of well-seasoned wood, carefully finished, and they kept accurate time. At an early date Philadelphia had also acquired a high character for clock-making; and some years before the Revolution, the celebrated David Rittenhouse, of that city, made calendar clocks which gained him the praise of the most skillful mechanicians in Europe.

C. C. of Texas.—We do not profess the practice of physick, nor do we take diagnosis of diseases—these offices belong to the professional physician; but we can tell you how to prepare a liniment that may be useful in removing your rheumatic pains.—Take one pint of brandy (we don't mean the stuff commonly sold as

Scientific American.

7

brandy), one ounce of gum camphor, one ounce of salt-peter, and one pint beef's gall, thoroughly mixed, and briskly applied to the surface either with the hand or with a soft flannel. It may do you no good, but it has helped some of our friends very much.

T. W. H., of Ill.—In the case you mention of lightning leaving the rod and passing from the tin roof to the bell wires of the house, we are inclined to think that the rod was imperfect. Our reason for supposing that lightning rods should not be disconnected from roofs was, that should the flash strike the roof, the rod would conduct it away; and in our opinion it would never leave a good conducting rod to go to a painted roof.

INVENTOR.—You had better have put your case into our hands at first. Depend upon it, no patent agency can be successful without an efficient branch at Washington. We do not, under any circumstances, trust any of our cases in the hands of other agents. Our office in Washington is under the care of the same firm as the one in this city; therefore no outside examination or exposure is possible. We would caution all inventors to beware not to allow their cases to pass through too many hands.

A. S. M., of Ill.—The patent law does not prescribe any penalty for selling an unpatented article for a patented one, except where such article is stamped or otherwise marked with the word "patent," or like device, with a view of imitating the mark or stamp of an existing patent or of a patentee, or with a view of deceiving the public, in which case the offending party is liable to a penalty of \$100—one-half to go to the party who shall sue for the same.

R. L. S., of N. Y.—We do not know of any machine in use for cutting up rough tallow. You had better explain to us more fully what you want, and we will see what can be done for you.

C. C. of N. Y.—You could scarcely truss up an older contrivance for a water wheel than to employ a series of buckets upon an endless chain. It won't do. You have now tried twice without success, but do not be discouraged. You have some inventive genius, but it needs nourishment.

H. W., of N. Y.—Address a letter to the care of the party whose address we last gave you.

G. H., of Va.—You had better prepare and send us an advertisement, and no doubt you will have your wants supplied. We are surprised to learn that the State of Virginia has no State Chemist.

A FARM of eight hundred acres was sold in England the other day for the enormous sum of two hundred dollars per acre.

THE STATE TRADE.—From one district in North Wales 120,000 tons of slate are annually exported.

The bells of the organ in Carlisle (Eng.) Cathedral is blown by water power.

G. A. G., of Ala.—A disinfectant used in the British navy is a highly concentrated solution of chloride of zinc, which is certainly preferable to chloride of lime, where the corrosive power or strong odor of the latter is objectionable, as in the sick chamber or close ship.

S. W. Y., of R. I.—Your sketch represents a pneumatic telegraph composed of a long line tube furnished with a glass tube at each end, in which a piston is forced to move in the air and operate signals, by mercury rising and falling to certain heights, indicated by letters of the alphabet. It is wholly unsuited for practical purposes, and there is little that is new in its design. A hydraulic telegraph on the same principle was proposed to us several years since.

H. L., of Ohio.—In the list of patents that appear in this paper thirty-five were granted to inventors whose applications were presented through the Scientific American Patent Agency. It is a fact worthy of note that no similar agency in the world has ever taken the same number of patents in one week. We have a strong force, and are able to bestow the utmost care upon all our cases. You can depend upon it that what we cannot obtain for you is scarcely worth undertaking to get elsewhere.

HUMAN HAIR.—There are two hundred thousand lbs. weight of women's hair annually sold in France, and the price paid for it is usually six cents an ounce.

OTSTAR OF ROSE.—One hundred thousand roses are required to give a yield of 125 grains of otstar, or oil of roses.

W. J. S., of N. Y.—Walker's arrangement for conducting lightning from telegraph lines, to prevent overcharges from destroying the magnets, &c., is described on page 191 of "Turnbull on the Electric Telegraph."

M. F., of Boston.—We have received your first article; it is excellent. Be pleased to furnish the others as soon as possible, so what we may have them all on hand when we commence to publish.

H. C. of N. J.—The "band and pulley brake" for stopping railroad trains was invented nearly twenty years ago by George S. Gregg, of Roxbury, Mass. It was first applied by the Boston and Worcester Railroad.

ENGINEER.—The first cost of English railroads is much greater than in this country, but this difference is more than made by the greater economy of the English lines. In the consumption of fuel alone the difference in favor of the English roads is about sixty per cent. The average cost of fuel on our lines is \$16,000,000, on the English, \$7,500,000. The difference in annual expense is \$71,000,000 in favor of English lines.

C. G., of N. Y.—asks if we can explain the reason "why a person is taller in the morning than at night." This difference is said to be about half an inch, and is owing to the relaxation of the cartilages.

G. A., of Mass.—You are wrong. The steamer Lexington was burned on the evening of the 18th of January, 1840. Some cotton in bales was stored around the smoke pipe, and it took fire, and although within sight of land, all but four persons on board perished. The number of persons lost was nearly 150.

S. W. B., of N. Y.—The method exhibited in your sketch of adjusting the beam of a plow by a transverse slot and bolt in the standard is not new. Brown's poly-chromatic printing press we consider a superior invention; but you must judge for yourself as to the pro-

priety of engaging in its manufacture. We cannot decide such questions.

Moncy received at the Scientific American Office on account of Patent Office business, for the week ending Saturday, September 4, 1858:—

C. P. S. of S. C., \$25; E. A. G., of Pa., \$50; G. M., of Mass., \$25; M. & E., of Ill., \$20; W. W., of Del., \$55; A. E. & S. N. McG., of Minn., \$12; W. H. B., of N. Y., \$20; W. B. C., of Pa., \$25; A. H. W., of N. Y., \$25; W. & J., of Conn., \$25; J. B. Jr., of Mass., \$25; M. & F., of Mass., \$20; A. P., of Mass., \$25; A. McV., of Ohio, \$20; H. & P., of N. Y., \$20; E. S., of Vt., \$20; J. R. McM., of N. Y., \$25; J. L. B., of N. Y., \$25; P. M., of Mich., \$25; G. S., of Mo., \$25; C. L. R., of Pa., \$25; W. H., of N. Y., \$25; W. H., of Pa., \$20; J. R. II., of Conn., \$20; A. B., of Vt., \$20; J. H. C., of N. Y., \$100; H. C. S., of Ohio, \$10; J. F. B., of Ill., \$25; G. B., of Mo., \$20; S. B. R., of Wis., \$25; P. W. G., & Co., of Ill., \$25; L. W. H., of N. Y., \$20; W. M., of N. Y., \$25; H. N. B., of N. Y., \$12; J. H. L., of N. Y., \$57; K. & R., of Mass., \$20; H. & M., of N. Y., \$20; W. G., of N. Y., \$25; C. J. C. P., of Iowa, \$60; W. T. F., of Tenn., \$44; J. M., of Wis., \$25; W. S., of Pa., \$20; S. S. S., of Pa., \$20; J. E. R., of Ill., \$20; H. E., of Iowa, \$20; T. R., of N. Y., \$20; D. W. H., of Mo., \$20; J. A. W., of —, \$20; H. E., of N. J., \$20; W. S. W., of L. I., \$12; J. P. B., of N. Y., \$25. Specifications and drawings belonging to parties with the following initials have been forwarded to the Patent Office during the week ending Saturday, September 4, 1858:—

P. M., of Mich.; W. M., of N. Y.; E. U. B., of Wis.; G. F. & M. J., of N. Y.; A. E. & S. N. McG., of Minn.; W. H., of N. Y.; J. R., of Conn.; C. L. R., of Pa.; J. F. B., of Ill.; W. & J., of Conn.; A. P., of Mass.; J. L. B., of N. Y.; C. P. P., of S. C.; A. W. D., of Me.; H. H., of Ind.; W. T. F., of Tenn.; S. C. H., of N. Y.; W. S. W., of N. Y.; T. E. McE., of Pa.; G. & H., of Ill.; J. B. Jr., of Mass.; H. N. B., of N. Y.; J. C. of Wis.; J. P. B., of N. Y.; R. B. L., of N. Y.; I. B., of Texas; D. R. K., of Conn.; C. B. C., of R. I.; B. T. S., of Ill.; G. M., of Mass.; A. H. W., of N. Y.; G. F. & C., of Ill.; I. P. E., of Ind.; J. & R. McE., of N. Y.; A. N. McE., of Mo. Total, 35 cases.

VALUABLE HINTS TO OUR READERS.

It is well known to all our readers that we employ no traveling agents.

In order to become a subscriber to the SCIENTIFIC AMERICAN, enclose the money in letter, and address it to Munn & Co., 128 Fulton street, New York City. We depend upon our friends to aid us in getting subscribers and forwarding the names.

The safest way to send money is by a draft or check made payable to our order. It is more sure of reaching us than when sent in bank bills.

If bank bills are sent, we will assume the risk of them reaching us, when subscribers preserve a description of the bills, and take a Postmaster's receipt to show that the money has been mailed.

Many letters sent to us are without Post-office address or signature, and therefore cannot be answered. When you order the SCIENTIFIC AMERICAN, be careful to give the name of the Post-office, County, and State to which you wish the paper sent. And when you change your residence, and desire your paper changed accordingly, state the name of both Post-offices—where you have been receiving it, and where you wish it sent in future.

NUMBERS OF VOLUME XIII.

We cannot supply Nos. 22, 23, 24, 25, 26, 27, and 28 of the last volume, but we can furnish Vol. XIII. complete and bound for \$2.75. Postage, 90 cents.

A MERICAN AND FOREIGN PATENT SOLICITORS.—Messrs. MUNN & CO., Proprietors of the SCIENTIFIC AMERICAN, receive applications for patents in the United States and all foreign countries on the most liberal terms. Our experience is of thirteen years' standing, and our facilities are equalled by any other agency in the world. The long experience we have had in preparing specifications and drawings has rendered us perfectly conversant with the mode of doing business at the United States Patent Office, and with most of the inventions which have been patented. Information concerning the patentability of inventions is freely given, without charge, on sending a model, drawing and description to our office.

SHEARS! SCISSORS! SCISSORS!—WENDT & SEYMOUR, Hoe & Co.'s Building, 31 Gold street, New York. Manufacture and have for sale Shears and Scissors of every description of the best quality and finish, with silver-plated or japanned handles.

ENGRAVING OF EVERY DESCRIPTION—Machinery, Patents, Maps, &c., by W. M. J. BAR-KER, No. 23 North Sixth street, Philadelphia, Pa. 1 4th

PICKPOCKETS FOILED—A NEW THING.—Sells rapidly. Send stamp for agency.

1 1st DICKINSON & BATE, Hudson, Mich.

TO HARDWARE MERCHANTS—WE send (free of postage) for one stamp the experience of forty of the most prominent agriculturists in the United States in the use of Gould's Patent Husking Thimbles, also the experience of agents in their sale, our terms to the trade, &c. And for one dollar, six sets of the thimbles (assorted sizes), with directions for using, &c., will be sent. Money sent by mail at our risk. Address J. H. GOULD & CO., Sole Proprietors, Alliance, Ohio.

HARRISON'S GRIST MILLS—20, 30, 36 AND 48 inches diameter, at \$100, \$200, \$300 and \$400, with all the modern improvements. Also, Portable and Stationary Steam Engines of all sizes, suitable for said Mills. Also, Bolters, Elevators, Belting, &c., &c. Apply to S. C. HILLS, 12 Platt st., New York. 1 1st

FIFTH EDITION—CATALOGUE CONTAINING 250 illustrations of Mathematical, Optical and Philosophical Instruments, with attachment of a large sheet representing the Swiss Instruments in their actual size and shape, will be delivered, on application to all parts of the United States, by sending 12 cents to C. T. ALMSLER, No. 635 Chestnut st., Philadelphia.

BAY STATE PLANER AND MATCHER, with wrought iron cutter-head and Fifth Planer Feed Works to surface, 54 inches wide, made by J. A. FAY & CO., Worcester, Mass. 1 4th

READ THIS—HUGHES' MISSOURI HAND Corn Planter—took first premium at United States Fair, September, 1857, in test—now challenges all others. Patented November, 1855, and September, 1857. County and State rights for sale. Send for a circular. Real estate taken in exchange for rights. Address D. W. HUGHES, Palmyra, Mo. 1 5th

GREAT FAIR OF THE AMERICAN INSTITUTE—held at the Crystal Palace—Articles will be received and located on and after Tuesday, September 7th. Entrance on Fortieth st. Exhibitors are requested to send their articles without delay.

1 2 F. W. GEISSENHAINER, Jr., Chairman.

BALLOONS FOR SALE—TWO NEW BALLOONS in complete order for ascensions. One of 1,000 lbs. power, the other 400 lbs. Apply to JOHN WISE, Lancaster, Pa. 1 4th cow

SECOND-HAND MACHINISTS' TOOLS.

VIZ. Engine and Hand Lathe, Iron Planer, Drills, Chuck Lathe, Gear Cutter and Vises, all in good order, and for sale low for cash. Also one new first-class Woodworth Planing and Matching Machine. Address FRANKLIN SKINNER, Agent, 14 Whitney avenue, New Haven, Conn. 1 13

CORLISS' PATENT STEAM ENGINES.

About 250, most of them from 40 to 400 horse power, are now in operation. On application, pamphlets will be sent (by mail), containing statements of responsible manufacturing companies where these engines have been furnished, for the saving of fuel, time, &c., varying from 2% to 5 years. Boilers, shafting, and gearing.

CORLISS STEAM ENGINE CO.

1 4th Providence, R. I.

WOODBURY'S IMPROVED WOODWORKING

Planing, Tonguing and Grooving Machines, are warranted to be vastly superior to any other machines in this country. When exhibited, they have always received the highest premium. Two gold medals have been awarded to the inventor, and one has been granted to another for improvements on these machines.

All sizes constantly for sale, by WM. BURTON, 189 Sudbury street, Boston. 1 8th

RIVETS.—IRON BRIDGE, SHIP GIRDER,

Boiler, Tank, Tender, Gasometer, and Stove Rivets.

Railroads, Locomotive and Machine Shops, Gasometer Manufacturers, &c., supplied with every kind of rivet used in the trade.

PHILLIPS & ALLEN, Rivet Works, Pennsylvania Avenue, west of 22d st., Philadelphia. 1 4th

ENGRAVING ON WOOD AND MECHANICAL

CAL DRAWING, by RICHARD TEN EYCK, Jr., 128 Fulton street, New York, Engraver to the Scientific American. 1 4th

CRIDGE, WADSWORTH & CO., MANUFACTURERS

of improved Patent Oscillating Steam Engine, with variable governor cut-off. Shop, county, and State rights for sale. Also one-half the patent for Great Britain. For illustration, see Sci. Am., Vol. 13, No. 51. Circulars with testimonials, &c., sent by mail on application to CRIDGE, WADSWORTH & CO., Pittsburgh, Pa. 1 8th

IRON AND COMPOSITION CASTINGS.

Chilled Rolls, Mill Gearings, Fan Blowers, Triv. Hammers, Shaving Shears, Presses, India Rubber Calenders, Grinding and Cutting Machines, Turbine and Center-vent Water Wheels, also contracts made for Breast and Overshot Wood Wheels, also orders taken for the manufacture of patented machinery of all kinds, by the BIRMINGHAM IRON FOUNDRY, Birmingham, Conn.

1 4th SHELDON BASSETT, President.

EVERY MILLWRIGHT, ALL MILL-

OWNERS, and those interested in hydrodynamics, should become acquainted with the merits and principles of the Improved Turbomeadow Water Wheel, or "Universal Pump," a wheel the most economical in the use of water, and giving the highest percentage, with a partially raised gate, or any yet discovered.

It gives from 75 to 97 per cent of power, according to the size of wheel and head employed. For information address S. K. BALDWIN, Laconia, N. H.

N. B.—For low falls of one, two, or three feet, also for any fall, it will surpass all others. 1 1st

THIRTIETH ANNUAL FAIR OF THE

AMERICAN INSTITUTE at the Crystal Palace, in the city of New York.—The Managers announce that the Exhibition will be opened on Wednesday, the 15th day of September next. The Palace will be prepared for the reception of goods on and after the 2d of Sept. Machinery and household articles will be exhibited from the 1st of July. This exhibition is intended to embrace Machinery and New Inventions, Manufacturers of all descriptions, and Agricultural and Horticultural Productions of every kind. Gold, silver and bronze medals, silver cups, and diplomas will be awarded on the report of competent and impartial judges. The Managers would impress upon exhibitors the importance of making early application for the space they wish to occupy. Circulars containing full details will be had by applying to WM. B. LEONARD, Corresponding Secretary of the Institute, No. 351 Broadway, New York, to whom all entries should be addressed. By order of the Managers, F. W. GEISSENHAINER, JR., Chairman. JOHN W. CHAMBERS, Secretary. 1 1st

SHEARS! SCISSORS! SCISSORS!

WENDT & SEYMOUR, Hoe & Co.'s Building, 31 Gold street, New York. Manufacture and have for sale Shears and Scissors of every description of the best quality and finish, with silver-plated or japanned handles.

1 1st

ENGRAVING OF EVERY DESCRIPTION

—Machinery, Patents, Maps, &c., by W. M. J. BAR-KER, No. 23 North Sixth street, Philadelphia, Pa. 1 4th

PICKPOCKETS FOILED—A NEW THING.

Sells rapidly. Send stamp for agency.

1 1st DICKINSON & BATE, Hudson, Mich.

TO HARDWARE MERCHANTS—WE

send (free of postage) for one stamp the experience of forty of the most prominent agriculturists in the United States in the use of Gould's Patent Husking Thimbles, also the experience of agents in their sale, our terms to the trade, &c. And for one dollar, six sets of the thimbles (assorted sizes), with directions for using, &c., will be sent. Money sent by mail at our risk. Address J. H. GOULD & CO., Sole Proprietors, Alliance, Ohio.

1 1st

HARRISON'S GRIST MILLS

—20, 30, 36 AND 48 inches diameter, at \$100, \$200, \$300 and \$400, with all the modern improvements. Also, Portable and Stationary Steam Engines of all sizes, suitable for said Mills. Also, Bolters, Elevators, Belting, &c., &c. Apply to S. C. HILLS, 12 Platt st., New York. 1 1st

FIFTH EDITION—CATALOGUE CONTAINING

250 illustrations of Mathematical, Optical and Philosophical Instruments, with attachment of a large sheet representing the Swiss Instruments in their actual size and shape, will be delivered, on application to all parts of the United States, by sending 12 cents to C. T. ALMSLER

Science and Art.

Extraction of Silver from Copper Ores.

Kocubly, in speaking of the extraction of silver from copper ores, at the Malden Smelting Works, near Freiberg, says that the process observed is an economical and efficient one. The copper stone, containing from 50 to 70 per cent of copper, 8 to 15 per cent of lead, and 0.20 to 0.45 per cent of silver, is stamped, sifted, and roasted in a double furnace with two hearths, one above the other, first in the upper hearth and then in the lower one. During the first stage of the roasting, sulphides of copper are converted into neutral and basic sulphates, which are again decomposed during the second stage of the roasting, giving off sulphuric and sulphurous acids, and being for the most part converted into oxyd of copper, while sulphate of silver and a small portion only of the sulphate of copper remains undecomposed. The roasted mass is again stamped and ground, and mixed with from 4 to 8 per cent of chloride of sodium, and again roasted. By this means the copper is converted into chloride, and chlorine compounds of the other metals are also produced. After this roasting is finished the mass is extracted in wooden tubs, under hydrostatic pressure. At first, lukewarm water is used for this purpose, and when the greater part of sulphate of soda and other salts have been removed a solution of chloride of sodium is substituted. This dissolves the chloride of silver into precipitating tanks containing copper, which is dissolved while the silver is precipitated.

Lockjaw in Horses.

This is a terrible malady to which horses are sometimes subject, and it is generally fatal owing to the want of skill on the part of veterinary physicians. The method pursued by them in its treatment has been blistering, clystering, &c., which rather aggravates than relieves the spasms that usually attend it. Death generally ensues by this practice, and the disease has been held to be almost incurable. In a late number of the Edinburgh *Veterinary Review*, a new system of managing lockjaw is described, and nearly all the cases in which it has been applied, have resulted favorably. The plan consists of a hot water packing similar to that pursued in the "water cure" for the *genus homo*.

As soon as the horse is observed to be affected with tetanus, it is wrapt from head to tail in four or five pairs of blankets, which have been wrung out of warm water at a temperature of 200° Fah. The animal is then allowed perfect rest and quietness for about two hours, when warm water of the above temperature is poured along its back outside of the blankets, and another like period of repose allowed, and so on until a cure is effected. A thin gruel of flour, oat, or Indian corn meal is given, when the jaws of the animal are capable of being opened.

As horses are liable to take lockjaw from pricks in the feet caused by careless or unskillful blacksmiths while shoeing them, this simple method of managing the disease can be applied by any person, and is designed, we think, to be of considerable benefit.

Improved Boiler Furnace.

This is an arrangement of fire bridges in the bed of a furnace designed for heating a double cylindrical boiler, so that the gases and products of combustion may pass off quickly, and give up nearly all their heat to the boilers in their passage under it. The fire-place or grate is made gradually tapering in order to prevent the escape of any gases that are unconsumed.

In our illustrations, Fig. 1 is a perspective view of the hearth and fire-place, with the boilers removed, and Fig. 2 is a vertical cross section of the furnace, with the boilers in their place.

A are the grate bars, and B the sloping

sides of the fire-place. C is the outer wall of the furnace, which is hollow, having a passage, g, throughout its length. This passage communicates with the external air by passages or holes, h, that can be closed or opened by doors, i, so as to admit a greater or less quantity of air to the fire, as desired. The

air entering any of these doors becomes heated in its passage through g, and passing through j into the chamber, k, is presented to the fire in a heated state, which is one of the best for obtaining proper combustion. The two boilers, G, are supported on side bridges, E, and central bridges, D, arranged as shown

sufficient force to prevent the slats from casually turning, and that the bar, E, is not in such a position as to obstruct the light, or to be liable to detachment from the slats or in any manner produce the inconvenience experienced in the use of the ordinary method of attaching and operating window blind slats.

The patent for this effective attachment to window blinds, for which there is a universal demand, was patented by Andrew Ferber, of Elizabeth City, N. J., on July 27th, 1858. Any further information can be had by addressing him.

Literary Notices.

WELLS' PRINCIPLES AND APPLICATIONS OF CHEMISTRY. By David A. Wells, A. M. New York: Ivison & Phinney, 221 Broadway. Every contribution to the natural sciences is an addition to our knowledge, and all those books which try to make the thorny paths of science easy and pleasant to the student are to be accepted with thanks. This book is the last published of a series by Mr. Wells, and is highly recommended by some eminent educational authorities. It embodies in a clear and forcible language easily understood, the facts of chemical science, illustrated with 240 engravings. From the number of professors and teachers who endorse the value of Mr. Wells' publications, they must be largely in use in our schools and colleges, and by those who use them as text-books, and many others, we have no doubt this new one will be hailed with pleasure.


THE KNICKERBOCKER. John A. Gray, 16 and 18 Jacob street, New York. We have received the September number of this veteran journal of upwards of half a century, and find it filled with that choice and versatile character of writing for which it has long been distinguished. This number is adorned with a finely executed likeness of Epes Sargent, whose writings have so frequently added lustre to this sterling magazine. It contains contributions from the graphic pens of Tuckerman, Stoddard, Aldrich, and other eminent writers. There is in addition a variety of other original matter, which renders its perusal highly useful and entertaining, including, of course, the rich, ripe and rosy, and genuine witty talk of the able editor, Lewis Gaylord Clark.

THE ECLECTIC MAGAZINE. W. H. Bidwell, editor and proprietor, 5 Beekman street, New York. The September number of this excellent periodical contains some of the best articles, as in fact every number does, of the foreign reviews. We may mention as best, "Description of Active and Extinct Volcanoes," "Recent Astronomy," and "Canning's Literary Remains." There are two portraits, one of David Garrick and his wife, and another of the Rev. Chas. Kingsley.

THE ATLANTIC MONTHLY. Phillips, Sampson & Co., Boston. The September number is an excellent one. The articles on "Eloquence," "Daphnaeides" and "An Evening with the Telegraph Wires," are particularly interesting. The "Autocrat of the Breakfast Table" is as lively, entertaining and philosophical as usual.


SKELLY'S BOILER FURNACE.

Fig. 1



in Fig. 2, and the gases and products of combustion, passing in the direction of the arrows to the flue, F, give up their heat to the boiler, being detained long enough to impart more heat than is usual, and at the same time, by

Fig. 2



this arrangement, the draft of the furnace is not materially impaired.

The simplicity of this device must recommend itself to every furnace builder. Any further particulars can be obtained by addressing the inventor, Evan Skelly, of Plaquemine, Aberville District, La. He has applied for a patent.

Pure Air.

The Eclectic Medical Journal of Philadelphia, in speaking on this subject, very properly remarks that it is not only necessary that men may have sufficient air to breathe, but it is necessary to provide air for the apartment itself in which they live, as well as for the persons who inhale it. The influence of impure air is not only exercised upon persons through their breathing organs, but the surface of their bodies, their clothes, the walls of the apartment—in short, the free surfaces of everything in contact with the air of the place becomes more and more impure—a harbor of foulness, a means of impregnating every cubic foot of air with poison—unless the whole apartment has its atmospheric contents continuously changed, so that everything animate and inanimate is freshened by a constant supply of pure air.

Ferber's Improved Window Blind.

This simple contrivance consists in fitting to one of the stiles of the window a vertical rod or bar, and attaching pins at the ends of the slats to openings in the same, whereby the rod cannot obstruct the light nor serve as encumbrances, as hitherto, nor the slats be allowed to turn or move casually. Through this means the appearance of the blind is not only greatly improved, but its attachments are made more durable than those of the usual construction.

In our illustrations Fig. 1 is a perspective view of the hearth and fire-place, with the boilers removed, and Fig. 2 is a vertical longitudinal section through a portion of the same, and Fig. 3 is a perspective view of the sliding bar

of ditto. The same letters in the figures indicate corresponding parts.

A represents the rectangular frame of a blind, on one stile of which is formed a rebate, B. C are the blind slats, the ends of which have journals formed on their centers, which turn in suitable boxes in the stiles, the journals, C', at one end being provided with radial arms or pins, D, which enter spaces, F, formed in a vertically sliding bar, E, fitted outside the rebate, and having a stop block, E', hinged to its lower end, which is capable of being pressed under the same when it is desired to sustain the said bar at its greatest height, to give a certain degree of inclination

Fig. 1




Fig. 2





Fig. 3



to the slats, or withdrawn from under the bar E, when it is desired to reverse their inclination. This bar is guided in its up-and-down movement by a spring plate, G, secured at one end to the stile of the window frame, and pressing at its opposite elastic end on a vertical rod or rib, H, attached to the outside of the bar, E.

From the above description it will be seen that when the bar, E, is moved up and down, the blind slats will be opened and closed by the spaces, F, in the same on the radial pins or arms, D, and that the elastic plate, G, will press against the guide rod or rib, H, with

This valuable and widely circulated journal entered upon its FOURTEENTH YEAR on the 11th of September.

It is an Illustrated Periodical, devoted to the promulgation of information relating to the various MECHANICAL and CHEMICAL ARTS, MANUFACTURES, AGRICULTURE, PATENTS, INVENTIONS, ENGINEERING, MILL WORK, and all interests which the light of PRACTICAL SCIENCE is calculated to advance.

All the most valuable patented discoveries are delineated and described in its issues, so that, as respects inventions, it may be justly regarded as an *Illustrated Repertory*, where the inventor may learn what has been done before him in the same field which he is exploring, and where he may publish to the world a knowledge of his own achievements.

Reports of American Patents granted are also published every week, including official copies of all the PATENT CLAIMS. These Patent Claims are furnished from the Patent Office Records expressly for this paper, and published in the SCIENTIFIC AMERICAN in advance of all other publications.

The contributors to the SCIENTIFIC AMERICAN are among the most eminent scientific and practical men of the times. The editorial department is universally acknowledged to be conducted with great ability, and is distinguished, not only for the excellence and truthfulness of its discussions, but for the fearlessness with which error is combated and false theories are exploded.

Mechanics, Inventors, Engineers, Chemists, Manufacturers, Agriculturists, and people in every profession of life, will find the SCIENTIFIC AMERICAN to be of great value in their respective callings. Its counsels and suggestions will save them hundreds of dollars annually, besides affording them a continual source of knowledge, the value of which is beyond pecuniary estimate.

TERMS OF SUBSCRIPTION—Two Dollars a Year, or One Dollar for Six Months.

CLUB RATES.

Five Copies, for Six Months.....	\$4
Ten Copies, for Six Months.....	\$8
Ten Copies, for Twelve Months.....	\$15
Fifteen Copies, for Twelve Months.....	\$22
Twenty Copies, for Twelve Months.....	\$28

For all clubs of Twenty and over, the yearly subscription is only \$1.40. Names can be sent in at different times and from different Post Offices. Specimen copies will be sent gratis to any part of the country.

Southern, Western and Canadian money or Post Office stamp, taken at par for subscriptions. Canadian subscribers will please to remit twenty-six cents extra on each year's subscription, to pre-pay postage.

MUNN & CO., Publishers and Patent Agents,

No. 128 Fulton street, New York.

For all clubs of Twenty and over, the yearly subscription is only \$1.40. Names can be sent in at different times and from different Post Offices. Specimen copies will be sent gratis to any part of the country.

Southern, Western and Canadian money or Post Office stamp, taken at par for subscriptions. Canadian subscribers will please to remit twenty-six cents extra on each year's subscription, to pre-pay postage.

MUNN & CO., Publishers and Patent Agents,

No. 128 Fulton street, New York.